

LEGEND COIN MAT INSTALLATION AND MAINTENANCE

INSTALLATION

Surface should be relatively flat, smooth and level. Prior to installation the base should be thoroughly cleaned and any sharp objects removed. Sweep or brush area to remove all loose dirt and dust. Wipe up any oil and chemicals from the floor before installing coin mat.

Legend coin mat can be loose laid on a flat surface. Basic installation does not require flooring adhesive for proper application.

For special applications or professional installation with heavy loads or traffic, flooring adhesives (2-component solvent free polyurethane adhesive) are recommended to provide the desired stability.

Colour consistency of the tiles and the batch identity, control number on the package label, are to be checked before the installation.

Tiles can be installed in minutes, without the use of special tools. Interlocking modular tiles allow you to create a coin mat of any length and width.

Joining tiles together is very easy with a hammer or rubber mallet.



For custom fit, allow product to relax and lay flat in place before trimming around edges and corners. If product is used under extreme temperature conditions, the product may expand or contract about 1-2% after laying flat.



Take note of holes, posts, radiators etc.. Fit each mat into place and make necessary cuts with snap-off knife or secateurs.



CLEANING AND MAINTENANCE

The performance of coin mat is dependent how well it is maintained. Coin mat should be regularly cleaned and maintained to ensure that the mat maintains its effective performance, as well as ensuring a long life span for the product.

Regular cleaning of the mat is recommended in order to keep the mat looking new and maintaining a presentable interior.

Top surface of coin mat is easy to clean by using a vacuum cleaner.

Sweep or mop the surface of Legend mat regularly. Mild soaps and normal household detergents may be used. Do not leave harsh detergents or chemicals on product or wash into sewer system.

Normal household vinyl cleaners may be used to increase longevity and to remove stubborn debris. Certain automotive vinyl products may cause surface to become slippery. Use a non-slip vinyl protector such as a clean-and-shine floor cleaner.

Legend coin mat is not a stain-proof product—certain dyes, inks, rubber tires, and chemicals may cause permanent staining.

Never use harsh chemicals such as tar remover or kerosene on this coin mat.

After cleaning, apply a coat of floor polish for vinyl floors to add a long-lasting, high-luster finish.

Leaving chemicals on the coin mat for a long period of time may cause damage. If concrete floor has been treated with certain sealers prior to mat installation, sealer may break down over time and adhere to back of mat without causing damage to mat.

Any floor surface can become slippery in the presence of moisture and debris. Proper care and cleaning of vinyl flooring will reduce the likelihood of slips and falls.

Connections of modular tiles should be checked regularly and damaged tiles should be replaced immediately. Due to interlocking modular system, it is very easy and inexpensive to replace a damaged coin mat tile with a new one.

